



## Provides Scalable, Secure, and Robust platforms for end-to-end security solutions.

The ISS NVR line provides scalable, secure, and robust platforms for end-to-end security solutions. It is optimized to run our industry-leading SecurOS® Video Intelligence Platform and designed for small- to large-scale deployments with large camera counts and bandwidth requirements in mind. Additionally, the NVRs are engineered to efficiently run ISS video analytics modules and to support SAN/NAS expansions.

The SecurOS® Edge Appliance 120 Series offers compact and highly reliable appliances, designed to provide efficient processing at the edge. Equipped with an Intel® Celeron® processor, these appliances can handle up to 8 SecurOS® VMS channels simultaneously. In addition, the units have built-in storage allowing for up to 5 days of video retention, depending on the model selected. The units also include a VPN client designed to work in virtually any network environment. This ensures a secure and reliable connection to the unit from remote locations, allowing for monitoring and control and efficient video surveillance. The SecurOS® Edge Appliance 120 Series is also compatible with our SecurOS® MCC (Monitoring Control Center) edition, making it an ideal choice for integrating into existing central monitoring centers.

Best in class components with a warranty to match, the SecurOS® NVR is designed to give you the power you need with the performance you can rely on. ISS tests, tunes, and guarantees that each NVR endures the toughest installations.



www.issivs.com

## **Specifications**

| op controlled to           |   |
|----------------------------|---|
| System                     |   |
| Windows                    | Windows 11 Pro / Linux Debian   |
| CPU                        | Intel® Celeron® J3455 (4 Cores, 4 Threads)                                    |
| RAM                        | 8GB DDR3  |
| Hard Drive                 | 512GB or 1TB  |
| Network                    | 2 x 1GbE NIC  |
| GPU                        | Intel® HD Graphics 500  |
| Video Outputs              | 2 x HDMI 1.4b (3840 x 2160 @ 30Hz)  |
| Temperatures               | Front: 2 x USB 3.0  Back: 2 x USB 3.0   |
| Warranty                   | 2-Year Parts Warranty   |
| Mechanical / Environmental |   |
| Form Factor                | Micro   |
| Power Supply               | AC 90-240V / DC 12V/40W   |
| Operating Temperature      | 32°F to 140°F (0°C to 60°C) with air flow                                     |
| Dimensions (WxDxH)         | 5.1" x 4.3" x 1.3" (129mm x 109.4mm x 34mm)                                   |
| Safety and Emissions       | CE, FCC, ErP for Barebone<br>CE, FCC, TUV, UL, CCC, CB, ErP for Power Adapter |
| Ordering Information       |   |
| NVR Part Numbers           | SOS-APP-120-512G, SOS-APP-120-1T  |



