



Provides Scalable, Secure, and Robust platforms for end-to-end security solutions.

The ISS NVR line provides scalable, secure, and robust platforms for end-to-end security solutions. It is optimized to run our industry-leading SecurOS® Video Intelligence Platform and designed for small- to large-scale deployments with large camera counts and bandwidth requirements in mind. Additionally, the NVRs are engineered to efficiently run ISS video analytics modules and to support SAN/NAS expansions.

Each NVR offers SATA storage and an Intel® Core™ processor for fast and stable performance. The onboard 12th/13th generation Intel® processor enables

up to 30% higher computing potential than its previous 11th generation processor counterparts. The NVR provides a complete video management, recording, and viewing solution in a single unit, to easily deploy a unified system combining video surveillance, access control, building automation, automatic license plate recognition, and other ISS video analytic modules.

Best in class components with a warranty to match, the SecurOS® NVR is designed to give you the power you need with the performance you can rely on. ISS tests, tunes, and guarantees that each NVR endures the toughest installations.



Enterprise Video & Analytics Servers Designed for Your Security and Business Needs. ISS | INTELLIGENT VIDEO. DEFINED.*

For more information visit our website: **WWW.ISSIVS.COM**

Specifications

System			
	Micro	SFF	Tower
Windows	Windows 11 Pro	Windows 11 Pro	Windows 11 Pro
СРИ	Intel® Core™ i3-13100T (4 Cores, 8 Threads)	Intel® Core™ i3-12100 (4 Cores, 8 Threads)	Intel® Core™ i3-12100 (4 Cores, 8 Threads)
RAM	8GB DDR4	8GB DDR4	16GB (2x8GB) DDR4
OS Drive	1 x 256GB M.2 NVMe SSD	1 x 256GB M.2 NVMe SSD	1 x 256GB M.2 NVMe SSD
Max. Data Storage	Up to 2TB SATA (1 X 2TB)	Up to 20TB SATA (1 X 20TB)	Up to 60TB Raw (3 x 20TB, SATA Drives)
Network	1 x 1GbE NIC	1 x 1GbE NIC	1 x 1GbE NIC
GPU	Intel [®] UHD Graphics 730	Intel [®] UHD Graphics 730	Intel [®] UHD Graphics 730
Video Outputs	1 x DisplayPort 1 x HDMI	1 x DisplayPort 1 x HDMI	2 x DisplayPorts 1 x VGA
USB	Front: 2 x USB 3.1 Gen 1 Rear: 2 x USB 3.1 Gen 1; 2 x USB 2.0	Front: 2 x USB 3.1 Gen1; 2 x USB 2.0 Rear: 2 x USB 3.1 Gen1; 2 x USB 2.0	Front: 2 x USB 3.2 Type A Gen2; 2 x USB 3.2 Type C Gen2 Rear: 2 x USB 2.0 Type A; 2 x USB 3.2 Type A Gen2; 2 x USB 3.2 Type A Gen1
Warranty	5-Year Next Business Day, Onsite Warranty	5-Year Next Business Day, Onsite Warranty	5-Year Next Business Day, Onsite Warranty
Accessories included	USB Keyboard, Mouse	USB Keyboard, Mouse	USB Keyboard, Mouse
Mechanical / Environmental			
Form Factor	Micro	Small Form Factor	Tower
		Small Form Factor 1 x M.2 SSD	Tower 1 x M.2 SSD
Form Factor	Micro		
Form Factor OS Drive Bays	Micro 1 x M.2 SSD	1 x M.2 SSD	1 x M.2 SSD
Form Factor OS Drive Bays Data Drive Bays	Micro 1 x M.2 SSD 1 x 2.5" Bay	1 x M.2 SSD 1 x 3.5" Bay	1 x M.2 SSD 3 x 3.5" Bay
Form Factor OS Drive Bays Data Drive Bays Power Supply	Micro 1 x M.2 SSD 1 x 2.5" Bay 65W	1 x M.2 SSD 1 x 3.5" Bay 200W	1 x M.2 SSD 3 x 3.5" Bay 460W
Form Factor OS Drive Bays Data Drive Bays Power Supply AC Input VAC Freq.	Micro 1 x M.2 SSD 1 x 2.5" Bay 65W 100 VAC to 240 VAC	1 x M.2 SSD 1 x 3.5" Bay 200W 100 VAC to 240 VAC	1 x M.2 SSD 3 x 3.5" Bay 460W 100 VAC to 240 VAC
Form Factor OS Drive Bays Data Drive Bays Power Supply AC Input VAC Freq. Operating Temperature	Micro 1 x M.2 SSD 1 x 2.5" Bay 65W 100 VAC to 240 VAC 41°F to 95°F (5°C to 35°C) 20% to 80%	1 x M.2 SSD 1 x 3.5" Bay 200W 100 VAC to 240 VAC 41°F to 95°F (5°C to 35°C) 20% to 80%	1 x M.2 SSD 3 x 3.5" Bay 460W 100 VAC to 240 VAC 32°F to 95°F (0°C to 35°C) 10% to 80%
Form Factor OS Drive Bays Data Drive Bays Power Supply AC Input VAC Freq. Operating Temperature Operating Humidity	Micro 1 x M.2 SSD 1 x 2.5" Bay 65W 100 VAC to 240 VAC 41°F to 95°F (5°C to 35°C) 20% to 80% (non-condensing) 1.4" x 7.0" x 7.2"	1 x M.2 SSD 1 x 3.5" Bay 200W 100 VAC to 240 VAC 41°F to 95°F (5°C to 35°C) 20% to 80% (non-condensing) 3.7" x 11.5" x 11.4"	1 x M.2 SSD 3 x 3.5" Bay 460W 100 VAC to 240 VAC 32°F to 95°F (0°C to 35°C) 10% to 80% (non-condensing) 6.89" x 17.12" x 14.17"
Form Factor OS Drive Bays Data Drive Bays Power Supply AC Input VAC Freq. Operating Temperature Operating Humidity Dimensions (WxDxH)	Micro 1 x M.2 SSD 1 x 2.5" Bay 65W 100 VAC to 240 VAC 41°F to 95°F (5°C to 35°C) 20% to 80% (non-condensing) 1.4" x 7.0" x 7.2" (36mm x 178mm x 182mm)	1 x M.2 SSD 1 x 3.5" Bay 200W 100 VAC to 240 VAC 41°F to 95°F (5°C to 35°C) 20% to 80% (non-condensing) 3.7" x 11.5" x 11.4" (97mm x 292mm x 290mm)	1 x M.2 SSD 3 x 3.5" Bay 460W 100 VAC to 240 VAC 32°F to 95°F (0°C to 35°C) 10% to 80% (non-condensing) 6.89" x 17.12" x 14.17" (175mm x 434.8mm x 359.9mm)
Form Factor OS Drive Bays Data Drive Bays Power Supply AC Input VAC Freq. Operating Temperature Operating Humidity Dimensions (WxDxH) Max. Weight	Micro 1 x M.2 SSD 1 x 2.5" Bay 65W 100 VAC to 240 VAC 41°F to 95°F (5°C to 35°C) 20% to 80% (non-condensing) 1.4" x 7.0" x 7.2" (36mm x 178mm x 182mm) 2.60 lbs (1.18 kg) Energy Star, CEC, CECP,	1 x M.2 SSD 1 x 3.5" Bay 200W 100 VAC to 240 VAC 41°F to 95°F (5°C to 35°C) 20% to 80% (non-condensing) 3.7" x 11.5" x 11.4" (97mm x 292mm x 290mm) 11.42 lbs (5.14 kg) Energy Star, CEC, CECP,	1 x M.2 SSD 3 x 3.5" Bay 460W 100 VAC to 240 VAC 32°F to 95°F (0°C to 35°C) 10% to 80% (non-condensing) 6.89" x 17.12" x 14.17" (175mm x 434.8mm x 359.9mm) 20.06 lbs (9.10 kg) Energy Star, CEC, CECP,
Form Factor OS Drive Bays Data Drive Bays Power Supply AC Input VAC Freq. Operating Temperature Operating Humidity Dimensions (WxDxH) Max. Weight Safety and Emissions	Micro 1 x M.2 SSD 1 x 2.5" Bay 65W 100 VAC to 240 VAC 41°F to 95°F (5°C to 35°C) 20% to 80% (non-condensing) 1.4" x 7.0" x 7.2" (36mm x 178mm x 182mm) 2.60 lbs (1.18 kg) Energy Star, CEC, CECP,	1 x M.2 SSD 1 x 3.5" Bay 200W 100 VAC to 240 VAC 41°F to 95°F (5°C to 35°C) 20% to 80% (non-condensing) 3.7" x 11.5" x 11.4" (97mm x 292mm x 290mm) 11.42 lbs (5.14 kg) Energy Star, CEC, CECP, FCC, UL	1 x M.2 SSD 3 x 3.5" Bay 460W 100 VAC to 240 VAC 32°F to 95°F (0°C to 35°C) 10% to 80% (non-condensing) 6.89" x 17.12" x 14.17" (175mm x 434.8mm x 359.9mm) 20.06 lbs (9.10 kg) Energy Star, CEC, CECP,
Form Factor OS Drive Bays Data Drive Bays Power Supply AC Input VAC Freq. Operating Temperature Operating Humidity Dimensions (WxDxH) Max. Weight Safety and Emissions Ordering Information	Micro 1 x M.2 SSD 1 x 2.5" Bay 65W 100 VAC to 240 VAC 41°F to 95°F (5°C to 35°C) 20% to 80% (non-condensing) 1.4" x 7.0" x 7.2" (36mm x 178mm x 182mm) 2.60 lbs (1.18 kg) Energy Star, CEC, CECP, FCC, UL	1 x M.2 SSD 1 x 3.5" Bay 200W 100 VAC to 240 VAC 41°F to 95°F (5°C to 35°C) 20% to 80% (non-condensing) 3.7" x 11.5" x 11.4" (97mm x 292mm x 290mm) 11.42 lbs (5.14 kg) Energy Star, CEC, CECP, FCC, UL	1 x M.2 SSD 3 x 3.5" Bay 460W 100 VAC to 240 VAC 32°F to 95°F (0°C to 35°C) 10% to 80% (non-condensing) 6.89" x 17.12" x 14.17" (175mm x 434.8mm x 359.9mm) 20.06 lbs (9.10 kg) Energy Star, CEC, CECP,
Form Factor OS Drive Bays Data Drive Bays Power Supply AC Input VAC Freq. Operating Temperature Operating Humidity Dimensions (WxDxH) Max. Weight Safety and Emissions Ordering Information NVR (Micro) Part Numbers	Micro 1 x M.2 SSD 1 x 2.5" Bay 65W 100 VAC to 240 VAC 41°F to 95°F (5°C to 35°C) 20% to 80% (non-condensing) 1.4" x 7.0" x 7.2" (36mm x 178mm x 182mm) 2.60 lbs (1.18 kg) Energy Star, CEC, CECP, FCC, UL SOS-NVR-150-1T-M, SOS-NVR-15 SOS-NVR-150-4T-S, SOS-NVR-15	1 x M.2 SSD 1 x 3.5" Bay 200W 100 VAC to 240 VAC 41°F to 95°F (5°C to 35°C) 20% to 80% (non-condensing) 3.7" x 11.5" x 11.4" (97mm x 292mm x 290mm) 11.42 lbs (5.14 kg) Energy Star, CEC, CECP, FCC, UL 0-2T-M 0-8T-S, SOS-NVR-150-12T-S, SOS-N	1 x M.2 SSD 3 x 3.5" Bay 460W 100 VAC to 240 VAC 32°F to 95°F (0°C to 35°C) 10% to 80% (non-condensing) 6.89" x 17.12" x 14.17" (175mm x 434.8mm x 359.9mm) 20.06 lbs (9.10 kg) Energy Star, CEC, CECP, FCC, UL



Copyright © 2023, ISS Corp. All rights reserved. Specifications in this document are subject to change. Sales Inquiries sales@issivs.com

Partner Portal support.issivs.com