



*Provides Scalable, Secure, and Robust platforms for end-to-end security solutions.* 

The ISS server line provides scalable, secure, and robust platforms for end-to-end security solutions. It is optimized to run our industry-leading SecurOS<sup>®</sup> Video Intelligence Platform and designed for small- to large-scale deployments with large camera counts and bandwidth requirements in mind. Additionally, the servers are engineered to efficiently run ISS video analytics modules and to support SAN/NAS expansions.

The SecurOS<sup>®</sup> Analytics Server 510 Series offers enterprise network video servers designed to run ISS video analytics modules. The 510 Series models support running ISS analytics in a low to medium capacity. These servers use Intel's latest generation processors to provide high-end performance and fast processing. In addition, the 510 Series models offer up to 120TB of storage, have redundant power supplies, and offer a number of extended support options. These servers provide a complete video management, recording, and viewing solution in a single unit, to easily deploy a unified system combining video surveillance, access control, and ISS video analytics.

Best in class components with a warranty to match, the SecurOS<sup>®</sup> Servers are designed to give you the power you need with the performance you can rely on. ISS tests, tunes, and guarantees that each server endures the toughest installations.



Enterprise Video & Analytics Servers Designed for Your Security and Business Needs. ISS | INTELLIGENT VIDEO. DEFINED.\*

For more information visit our website: **WWW.ISSIVS.COM** 

## **Specifications**

System	
Windows	Windows 11 Pro Windows Server 2022 (optional)
CPU	Intel® Xeon® Gold 6426Y (16 Cores, 32 Threads)
RAM	96GB (6 x 16GB) DDR5
OS Drive	2 x 480GB M.2 SSD (RAID1)
Max. Data Storage	Up to 120TB Raw (6 x 20TB, SATA Drives)
RAID	JBOD, 0, 1, 5, 6, 10
RAID Controller	PERC H755
Network	6 x 1GbE NIC
GPU	Integrated Matrox G200
Video Outputs	1 x VGA
USB	Front: 1 x USB 2.0; Rear: 1 x USB 2.0; 1 x USB 3.0
Remote Management	iDRAC Express
Warranty	5-Year Next Business Day, Onsite Warranty (Keep Your Own Hard Drives)
Accessories included	Rail Kit
Mechanical / Environmental	
Form Factor	2U Rackmount
Form Factor OS Drive Bays	2U Rackmount 2 x M.2 SSD
OS Drive Bays	2 x M.2 SSD
OS Drive Bays Data Drive Bays	2 x M.2 SSD 12 x 3.5" Hot Swap
OS Drive Bays Data Drive Bays Power Supply	2 x M.2 SSD 12 x 3.5" Hot Swap 2 x 1400W Hot Swap ( <i>2 x 1800W Hot Swap on select models</i> )
OS Drive Bays Data Drive Bays Power Supply AC Input VAC Freq.	2 x M.2 SSD   12 x 3.5" Hot Swap   2 x 1400W Hot Swap (2 x 1800W Hot Swap on select models)   100 VAC to 240 VAC, 50/60 Hz, Autoranging
OS Drive Bays Data Drive Bays Power Supply AC Input VAC Freq. Operating Temperature	2 x M.2 SSD   12 x 3.5" Hot Swap   2 x 1400W Hot Swap (2 x 1800W Hot Swap on select models)   100 VAC to 240 VAC, 50/60 Hz, Autoranging   50°F to 95°F (10°C to 35°C)
OS Drive Bays Data Drive Bays Power Supply AC Input VAC Freq. Operating Temperature Operating Humidity	2 x M.2 SSD   12 x 3.5" Hot Swap   2 x 1400W Hot Swap (2 x 1800W Hot Swap on select models)   100 VAC to 240 VAC, 50/60 Hz, Autoranging   50°F to 95°F (10°C to 35°C)   5% to 90% (non-condensing)
OS Drive Bays Data Drive Bays Power Supply AC Input VAC Freq. Operating Temperature Operating Humidity Dimensions (WxDxH)	2 x M.2 SSD   12 x 3.5" Hot Swap   2 x 1400W Hot Swap (2 x 1800W Hot Swap on select models)   100 VAC to 240 VAC, 50/60 Hz, Autoranging   50°F to 95°F (10°C to 35°C)   5% to 90% (non-condensing)   18.9" x 28.4" x 3.41" (482mm x 721.6mm x 86.8mm)
OS Drive Bays Data Drive Bays Power Supply AC Input VAC Freq. Operating Temperature Operating Humidity Dimensions (WxDxH) Max. Weight	2 x M.2 SSD   12 x 3.5" Hot Swap   2 x 1400W Hot Swap (2 x 1800W Hot Swap on select models)   100 VAC to 240 VAC, 50/60 Hz, Autoranging   50°F to 95°F (10°C to 35°C)   5% to 90% (non-condensing)   18.9" x 28.4" x 3.41" (482mm x 721.6mm x 86.8mm)   63 lbs (28.6 kg) Fully Populated
OS Drive Bays Data Drive Bays Power Supply AC Input VAC Freq. Operating Temperature Operating Humidity Dimensions (WxDxH) Max. Weight Safety and Emissions	2 x M.2 SSD   12 x 3.5" Hot Swap   2 x 1400W Hot Swap (2 x 1800W Hot Swap on select models)   100 VAC to 240 VAC, 50/60 Hz, Autoranging   50°F to 95°F (10°C to 35°C)   5% to 90% (non-condensing)   18.9" x 28.4" x 3.41" (482mm x 721.6mm x 86.8mm)   63 lbs (28.6 kg) Fully Populated



ISS | INTELLIGENT VIDEO. DEFINED.\*

Copyright © 2024, ISS Corp. All rights reserved. Specifications in this document are subject to change. Sales Inquiries sales@issivs.com

Partner Portal support.issivs.com